ZP-8404DWHT

WiFi 6 AX3000 DualBand CATV GPON Router

4GE+CATV+AX3000 GPON ONU

802.11ax2.4GHz	574Mbps
802.11ax5GHz	2402Mbps

IPv4 & IPv6
Dual stack

E/GPON Dual
Mode

Routing & Bridging
Mode

Dual Band 4*Antennas
AX 3000Mbps

Next-Gen Gigabit WiFi6
2.4GHz & 5GHz Dual Band
Speed up to 3Gbps

Tray-mounted Fiber Structure
Triple-play Services

ZP ELECTRON CO.,INC
Address: 438 JinCheng Road, XiaoShan District,Hang Zhou City, ZheJiang
Tel: +0086-571-82893391 Mobile Phone: +0086-13666654184
E-Mail: info@zpcable.com Skype: samzpcable Website: www.zpcable.com

Introduction

ZP-8404DWHT is 4GE+CATV+AX3000 with USB optional XPON(GPON and GEPON dual mode) HGU ONU.The device is fully comply with ITU-T G.984/G988 and IEEE802.3ah.The equipment integrates the reliability, maintainability and security design of carrier-grade level, and provioes customers with the last kilometer of broadband access to residential and corporate customers .It can also be applied to a strictly temperature environment, and can work stable for longtime without service interruption.

ZP-8404DWHT is interoperable with all brands of OLT and is Easy to install, provisioning and maintenance. The device can identify the working mode of the OLT to automatically complete the switch between GPON and EPON , The device can be freely switched between bridge and routing modes , and supports PPPoE dial-up and IPv6 functions in routing mode to meet the needs of different scenarios.

Application Chart



ZP ELECTRON CO.,INC
Address: 438 JinCheng Road, XiaoShan District,Hang Zhou City, ZheJiang
Tel: +0086-571-82893391 Mobile Phone: +0086-13666654184
E-Mail: info@zpcable.com Skype: samzpcable Website: www.zpcable.com

Product Parameters

Hardware Parameter	
Dimension	246mm×157mm×38mm（L×W×H）
Net weight	355g
Operating condition	• Operating temperature: -10 ~ +45°C • Operating humidity: 10 ~ 90% (non-condensing)
Storing condition	• Storage temperature: -40 ~ +70°C • Storage humidity: 5 ~ 95% (non-condensing)
Power adapter	DC 12V/1.5A, external AC-DC power adapter
Interfaces	XPON+4×GE+1×CATV+WiFi AX3000
Buttons	Reset,WPS
Indicators	Power, PON, LOS, Internet, LAN1-4, CATV,2.4G, 5G, WPS

Interface Parameter	
PON interface	• 1XPON port(EPON PX20+ and GPON Class B+) • PON standard: GEPON IEEE802.3ah, GPON ITU-T G.984 • SC single mode, SC/UPC or SC/APC connector • TX optical power: 0～4dBm(EPON) or 0.5～5dBm(GPON) • RX sensitivity: EPON: -27dBm GPON: -28dBm • Overload optical power: -3dBm(EPON) or - 8dBm(GPON) • Transmission distance: 20KM max • Wavelength: TX 1310nm, RX1490nm
LAN interface	• 4×GE Auto-negotiation RJ45 ports
CATV interface	• RF Optical power : +2～-18dBm • Optical return loss: ≥45 dB • Optical receiving wavelength: 1550±10nm • RF frequency range: 47～1000MHz • RF output impedance: 75Ω • RF output return loss: ≥14 dB • RF output level: ≥ 76±2dBuV(@-15~0dBm) • AGC range: 0～-15dBm • C/N: ≥47dB@-7dBm • CTB: ≥60dB@-7dBm • CSO: ≥60dB@-7dBm • MER: ≥35dB(-10dBm optical input)
WiFi interface	• Compliant with IEEE802.11b/g/n/ac/ax • WiFi: 2.4GHz 2×2, 5.8GHz 2×2 MIMO • 4*5dBi external antennas • Multiple SSID

ZP ELECTRON CO.,INC
Address: 438 JinCheng Road, XiaoShan District,Hang Zhou City, ZheJiang
Tel: +0086-571-82893391 Mobile Phone: +0086-13666654184
E-Mail: info@zpcable.com Skype: samzpcable Website: www.zpcable.com

Software Features	
PON	• XPON Dual Mode • SN and LOID+Password multiple registration methods
Layer2	• Support VLAN transparent/tag/translate/trunk • Support Layer 2 802.1Q VLAN, 802.1P QoS, ACL etc
Layer3	• IPv4, IPv6 and IPv4/IPv6 dual stack • Support bridge, router & bridge/router mixed mode • DHCP v4/v6 Client/Server, PPPoE & Static • Support Static Routing • Support hardware NAT
Multicast	• Support IGMP v2 and MLD proxy/ snooping • Support MultiCast VLAN & MultiCast Maximum Address
Security and Firewall	• DDoS, Filtering Based on ACL/ MAC/ URL • Support DDNS, ALG, UPnP, Port forwarding, DMZ • HTTP/ SSH/ Telnet Service Access Control • Support Parent control • Support PPTP , L2TP, Pass-through service
QoS	• Support 4 queues • Support SP, WRR, 802.1P and DSCP
WiFi	• Wi-Fi 6: 802.11a/n/ac/ax 5GHz & 802.11g/b/n/ax 2.4GHz • WiFi Encryption:WEP-64/WEP-128/ WPA/WPA2/WPA3 • Support WiFi Easy-mesh function
Management	• Support Telnet, CLI, OMCI/OAM ,TR069 and Web management

Package

Package	• 1 x ONU • 1 x Quick Installation Guide • 1 x Power Adapter

Ordering information

Product Name	Product Description	Accessories
ZP-8404DWHT	XPON+4GE+1CATV+WiFi AX3000	AC-DC power adapter: DC12V/1.5A

ZP ELECTRON CO.,INC
Address: 438 JinCheng Road, XiaoShan District,Hang Zhou City, ZheJiang
Tel: +0086-571-82893391 Mobile Phone: +0086-13666654184
E-Mail: info@zpcable.com Skype: samzpcable Website: www.zpcable.com