



ZP9414-UDWH

WiFi 5 AC1200 DualBand GPON Router

4GE+1POTS+USB2.0+AC1200 XPON ONU

802.11ax2.4GHz	300Mbps
802.11ax5GHz	900Mbps

Introduction

ZP9414-UDWH Series is 4GE+1POTS+USB2.0+AC1200 (POTS,USB optional) XPON(GPON and GEAPON dual mode) HGU ONU.The device is fully comply with ITU-T G.984/G988 and IEEE802.3ah. The equipment integrates the reliability, maintainability and security design of carrier-grade level, and provides customers with the last kilometer of broadband access to residential and corporate customers. It can also be applied to a strictly temperature environment, and can work stable for longtime without service interruption.

ZP9414-UDWH Series is interoperable with all brands of OLT and Easy to install, provisioning and maintenance. The device can identify the working mode of the OLT to automatically complete the switch between GPON and EPON, The device can be freely switched between bridge and routing modes, and supports PPPoE dial-up and IPv6 functions in routing mode to meet the needs of different scenarios.


ZP ELECTRON CO.,INC

Address: 438 Jincheng Road, Xiaoshan District, Hangzhou City, Zhejiang, China.

Tel: +86-571-83732728 Mobile Phone: +86-13666654184

E-Mail: info@zpcable.com Website: www.zpcable.com

Application Chart



Product Interface and LED

1. Power on the device



5. Connect WiFi and test speed



3. Connect Ethernet port, set up the services and browser internet



2. Plug in the fiber and register device to the OLT



4. (Optional) Connect telephone and check the service

ZP ELECTRON CO.,INC

Address: 438 Jincheng Road, Xiaoshan District, Hangzhou City, Zhejiang, China.

Tel: +86-571-83732728 Mobile Phone: +86-13666654184

E-Mail: info@zpcable.com Website: www.zpcable.com



Product Parameters

Hardware Parameter

Dimension	246mm×157mm×38mm (L×W×H)
Operating condition	• Operating temperature: -10 ~ +45°C • Operating humidity: 10 ~ 90% (non-condensing)
Storing condition	• Storage temperature: -40 ~ +70°C • Storage humidity: 5 ~ 95% (non-condensing)
Power adaptor	DC 12V/1A, external AC-DC power adaptor
Interfaces	XPON+4×GE+USB2.0+POTS+WiFi AC1200 (POTS,USB Optional)
Buttons	Reset,WPS
Indicators	Power, PON, LOS,Internet, LAN1-4, USB, 2.4G, 5G, TEL, WPS

Interface Parameter

PON interface	• 1XPON port(EPON PX20+ and GPON Class B+) • PON standard: GEAPON IEEE802.3ah, GPON ITU-T G.984 • SC single mode, SC/UPC or SC/APC connector • TX optical power: 0~4dBm(EPON) or 0.5~5dBm(GPON) • RX sensitivity: EPON: -27dBm, GPON: -28dBm • Overload optical power: -3dBm(EPON) or -8dBm(GPON) • Transmission distance: 20KM • Wavelength: TX 1310nm, RX1490nm
LAN interface	• 4×GE Auto-negotiation RJ45 ports
POTS interface(Optional)	• 1×RJ11 Connector
USB interface(Optional)	• 1×USB 2.0
WiFi interface	• Compliant with IEEE802.11b/g/n/ac • WiFi: 2.4GHz 2×2, 5.8GHz 2×2 MIMO • 4*5dBi external antennas • Multiple SSID

ZP ELECTRON CO.,INC

Address: 438 Jincheng Road, Xiaoshan District, Hangzhou City, Zhejiang, China.

Tel: +86-571-83732728 Mobile Phone: +86-13666654184

E-Mail: info@zpcable.com Website: www.zpcable.com



Software Features	
PON	• XPON Dual Mode • SN and LOID+Password multiple registration methods
Layer2	• Support VLAN transparent/tag/translate/trunk • Support Layer 2 802.1Q VLAN, 802.1P QoS, ACL etc
Layer3	• IPv4, IPv6 and IPv4/IPv6 dual stack • Support bridge, router & bridge/router mixed mode • DHCP v4/v6 Client/Server, PPPoE & Static • Support Static Routing • Support hardware NAT
Multicast	• Support IGMP v2 and MLD proxy/ snooping • Support MultiCast VLAN & MultiCast Maximum Address
Security and Firewall	• DDoS, Filtering Based on ACL/MAC/URL • Support DDNS, ALG, UPnP, Port forwarding, DMZ • HTTP/SSH/Telnet Service Access Control • Support Parent control • Support PPTP , L2TP, Pass-through service
QoS	• Support 4 queues • Support SP, WRR, 802.1P and DSCP
VoIP	• SIP and IMS SIP • G.711a/G.711u/G.722/G.729/G.723/G.726 Codec • Echo cancellation,VAD/CNG,DTMF Relay • T.30/T.38 FAX • Caller Identification/Call Waiting/Call Forwarding/Call Transfer/Call Hold/3-way Meeting conference • Line testing according to GR-909 • Support high-quality broadband voice
WiFi	• Integrated 802.11b/g/n/ac • Authentication:WEP/WAP-PSK(TKIP)/WAP2-PSK(AES) /WPA3/ WPA3 Transition • Modulation type:DSSS,CCK and OFDM • Easymesh



Management	• Support Telnet, CLI, OMCI/OAM ,TR069 and Web management
------------	---

Package

Package	• 1 x ONU • 1 x Quick Installation Guide • 1 x Power Adaptor
---------	--

Ordering information

Product Name	Product Description	Accessories
ZP9414-UDWH	XPON+4*GE+1*POTS+1*USB2.0+WiFi AC1200	AC-DC power adaptor: DC12V/1A
ZP9414-DWH	XPON+4*GE+1*POTS+WiFi AC1200	AC-DC power adaptor: DC12V/1A
ZP9404-DWH	XPON+4*GE+WiFi AC1200	AC-DC power adaptor: DC12V/1A

ZP ELECTRON CO.,INC

Address: 438 Jincheng Road, Xiaoshan District, Hangzhou City, Zhejiang, China.

Tel: +86-571-83732728 Mobile Phone: +86-13666654184

E-Mail: info@zpcable.com Website: www.zpcable.com

